

- WISE cam SERVER -

WEB SERVER SPECIFICATIONS

PRIMARY FEATURES

STAND ALONE TYPE

- NON PC BASED

EASY ACCESS

- NEED ONLY WEB BROWSER (INTERNET EXPLORER, NETSCAPE)

4 CHANNELS VIDEO INPUT

LOOP THROUGH OUTPUT (AUTO TERMINATION)

ALARM FUNCTION

VIDEO LOSS DETECTION

MOTION DETECTION

DVR FUNCTION THROUGH THE FTP

PRE / POST ALARM BUFFER

REMOTE PAN/TILT/ZOOM CONTROL

VARIOUS SCREEN SIZE

SINGLE/QUAD/SEQUENTIAL DISPLAY

SUPPORT OF VARIOUS NETWORK PROTOCOLS

NEW VERSION SOFTWARE UPDATES THROUGH TCP/IP NETWORK

DYNAMIC IP SUPPORT

NTSC / PAL COMPATIBLE

IMAGE COMPRESSION	Method	JPEG Compression
	Compression Level	4 Level
	Performance	Single 30 frame/sec. Quad 5 frame/sec.
IMAGE DISPLAY	Resolution	640 x 480, 320 x 240, 160 x 120
	LAN Interface	Ethernet (10/100 Base-T)
	Protocol	TCP, IP, ARP, RARP, HTTP, FTP, SMTP, DHCP, ICMP
	Operating System	Linux

	Hardware	CPU 32 bits RISC Processor Flash 8Mbyte DRAM 32Mbyte
	Software Upgrade	Flash memory allows new version software updates through TCP/IP network
	Security	Password Protection
INPUT / OUTPUT CONNECTORS	Video Input	BNC 4 Channels Video Input
	Loop Through Output	BNC 4 Channels Video Output (Auto Termination)
	P/T/Z Control	2 Pin Snap On Type
	Alarm IN/OUT	8 Pin Snap On Type
	Network Interface	RJ-45 CAT 5
	Power	DC Power JACK
ALARM	Input	4 Channels N.O / N.C Selectable
	Output	N.O / N.C Relay Output
PAN/TILT/ZOOM		RS-485
POWER REQUIREMENT		12V DC \pm 10%, 1A
POWER CONSUMPTION		12W MAX.
OPERATING CONDITION		0°C ~ 50°C, Less Than 90%RH
DIMENSIONS		218.0(W) x 44.0(H) x 155.0(D) mm
NET WEIGHT		1,100g

Ver. 0.5

LINUDIX Co., Ltd. 1303-34 Baekam Bldg, Seocho-Dong, Seocho-Gu SEOUL, KOREA 137-070 TEL : 82 - 2 - 3482 - 0991 / 0992 FAX : 82 - 2 - 3482 - 0993
